






## EYELAGS - DRILL POINT

Interior suspended ceiling systems into Steel  
Longer length for drywall (or insulation) into Steel.



ELDZ2

### Product Specifications



ELDZ3

Part #	Dia.	Length	TPI	Bulk Qty	Hole Dia.	Thread Length	Flange Dia.	Point	Finish
ELDZ2	1/4"	2"	14	1M	3/16"	3/4"	1/2"	SD/S12	Zinc
ELDZ3	1/4"	3"	14	1M	3/16"	2"	1/2"	SD/S12	Zinc

Eyelag Drill Point Screws Ultimate Connection Value Chart				
Part	Nominal Screw Dia. (in)	Shear Strength (Lbs)	Metal Gauge	Tension (Pull) Lbs 1 pc
ELDZ2	1/4"	2491	22	500
			20	847
			16	1043
			12	2273
ELDZ3	1/4"	3020	22	518
			20	891
			16	1035
			12	2101

#### Ultimate Value Chart

Screws driven into steel were driven with three exposed threads on the off side of the connection, then pulled out with testing machine.

Note that all results were obtained in strict adherence to ASTM test protocol. These ultimate figures are offered only as a guide and are not guaranteed in any way by PrimeSource Building Products. A 4:1 safety ratio is recommended.

**ALL PRIMESOURCE FASTENERS ARE MANUFACTURED IN AN ISO 9002 AND ISO 14001 CERTIFIED AND APPROVED FACTORY TO PRIMESOURCE PERFORMANCE SPECIFICATIONS AND PRINT DRAWINGS.**