






## HIGH & LOW THREAD DRYWALL SCREW

Drywall to steel. 20 gauge (33 mil) or less. Special applications requiring strip-out resistance



Meets  
ASTM C-1002  
Reduced #2 Phillips

### Product Specifications



Type S & W

Part #	Dia.	Length	TPI	Bulk Qty	Finish	Head	Head Dia.	Corrosion	Thread	Point
HL100	6	1	18	10M	Phosphate	Bugle	8.0 ~ 8.5mm	48 hr. min. B-117	High and Low	Piercing 25 °
HL118	6	1-1/8	18	10M	Phosphate	Bugle	8.0 ~ 8.5mm	48 hr. min. B-117	High and Low	Piercing 25 °
HL114	6	1-1/4	18	8M	Phosphate	Bugle	8.0 ~ 8.5mm	48 hr. min. B-117	High and Low	Piercing 25 °
HL158	6	1-5/8	18	5M	Phosphate	Bugle	8.0 ~ 8.5mm	48 hr. min. B-117	High and Low	Piercing 25 °
HL2	7	2	18	3.5M	Phosphate	Bugle	8.0 ~ 8.5mm	48 hr. min. B-117	High and Low	Piercing 25 °
HL214	7	2-1/4	18	3M	Phosphate	Bugle	8.0 ~ 8.5mm	48 hr. min. B-117	High and Low	Piercing 25 °
HL212	8	2-1/2	15	2.5M	Phosphate	Bugle	8.0 ~ 8.5mm	48 hr. min. B-117	High and Low	Piercing 25 °
HL3	8	3	15	2M	Phosphate	Bugle	8.0 ~ 8.5mm	48 hr. min. B-117	High and Low	Piercing 25 °

### Pro-Twist Marker® Multi-Purpose Screws Meet or Exceed ASTM C-1002 and/or ASTM C-1513

Dia.	Metal Gauge/1lb	Tension (Pull) Lbs. 1 Pc.	Shear Lbs. Metal to Metal
6	25	165	410
	22	245	601
	20	349	620
7	25	172	412
	22	260	625
	20	358	628
8	25	149	337
	22	196	591
	20	367	829

#### Ultimate Value Charts

Steel - Screws driven into steel were driven with three exposed threads on the off side of the connection, then pulled out with testing machine.

Note that all results were obtained in strict adherence to ASTM test protocol. These ultimate figures are offered only as a guide and are not guaranteed in any way by PrimeSource. A 4:1 safety ratio is recommended.

#### Installation Guidelines

0-2500rpm Screwgun with torque adjustment - Overdriving may result in fastener failure or stripout of the work surface

The fastener is fully seated when the head's bearing surface is flush with the drywall.

The fastener must penetrate beyond the metal a minimum of three threads to comply with the code

NOT Recommended for use with treated wood.

ALL PRIME SOURCE FASTENERS ARE MANUFACTURED IN AN ISO 9002 AND ISO 14001 CERTIFIED AND APPROVED FACTORY TO PRIME SOURCE PERFORMANCE SPECIFICATIONS AND PRINT DRAWINGS.