



# TECHNICAL DATA

## COLLATED FINE THREAD DRYWALL SCREW

For attaching gypsum board to 25-20 gauge steel studs.

### PRODUCT SPECIFICATIONS

| Part #    | Length | Point       | Gauge | Bit Size |
|-----------|--------|-------------|-------|----------|
| FS114C1M  | 1-1/4  | Sharp Point | #6    | #6       |
| FS114C4M  | 1-1/4  | Sharp Point | #6    | #6       |
| FS118C4M  | 1-1/8  | Sharp Point | #6    | #6       |
| FS158C1M  | 1-5/8  | Sharp Point | #6    | #6       |
| FS158C4M  | 1-5/8  | Sharp Point | #6    | #6       |
| FS6200C1M | 2      | Sharp Point | #6    | #6       |
| FS6200C4M | 2      | Sharp Point | #6    | #6       |



|                 | Size       | 4M        | 1M        |
|-----------------|------------|-----------|-----------|
| Black Phosphate | 6 x 1"     | -         | FS100C1M  |
|                 | 6 x 1-1/8" | -         | FS118C1M  |
|                 | 6 x 1-1/4" | FS114C4M  | FS114C1M  |
|                 | 6 x 1-5/8" | FS158C4M  | FS158C1M  |
|                 | 6 x 2"     | FS6200C4M | FS6200C1M |
|                 | 7 x 2"     | -         | FS200C1M  |
| Zinc            | 6 x 1"     | -         | FSZ100C1M |

- Bugle Head
- #2 Phillips Recess Drive
- Sharp Point
- Coarse Thread
- Available in Black Phosphate or Zinc
- Made to conform to ASTM C1002

For fastener technical assistance call 800-676-7777

ALL PRIMESOURCE® FASTENERS ARE MANUFACTURED IN AN ISO 9001 CERTIFIED AND APPROVED FACTORY TO PRIMESOURCE® PERFORMANCE SPECIFICATIONS AND PRINT DRAWINGS.