



TECHNICAL DATA


PARTICLE BOARD SCREWS

For all around wood-to-wood applications including ash, alder, beech, oak, mahogany, walnut, rosewood, teak, mdf board, osb board and other hardwoods. Also can be used for attaching wood products to light gauge (25-20 gauge) steel.



COMBO Drive

PRODUCT SPECIFICATIONS



Part #	Dia.	Length	TPI	Bulk Qty	Finish	Head	Head Dia.	Corrosion	Point
PBP08112	8	1-1/2 in.	10	5M	Zinc Plated	Flat Head with Nibs	8.0 mm ~ 8.5 mm	24 hr. min. B-117	Type 17 point
PBP08114	8	1-1/4 in.	10	6M	Zinc Plated	Flat Head with Nibs	8.0 mm ~ 8.5 mm	24 hr. min. B-117	Type 17 point
PBP08158	8	1-5/8 in.	10	5M	Zinc Plated	Flat Head with Nibs	8.0 mm ~ 8.5 mm	24 hr. min. B-117	Type 17 point
PBP08200	8	2 in.	10	3M	Zinc Plated	Flat Head with Nibs	8.0 mm ~ 8.5 mm	24 hr. min. B-117	Type 17 point
PBP08212	8	2-1/2 in.	10	2.5M	Zinc Plated	Flat Head with Nibs	8.0 mm ~ 8.5 mm	24 hr. min. B-117	Type 17 point
PBP08300	8	3 in.	10	2M	Zinc Plated	Flat Head with Nibs	8.0 mm ~ 8.5 mm	24 hr. min. B-117	Type 17 point

Particle Board Screws Ultimate Value Chart

Dia.	Pull Out Lbs (Particle Board)	Shear Strength (lbs)	Minimum Torsional Strength (in-lbs)
8	318	1023	39

Ultimate Value Charts

Wood – Screws driven 3/4" into the wood material, then pulled out the testing machine.

Note that all results were obtained in strict adherence to ASTM test protocol. These ultimate figures are offered only as a guide and are not guaranteed in any way by PrimeSource. A 4:1 safety ratio is recommended.

Installation Guidelines

0-2500rpm Screwgun with torque adjustment – Overdriving may result in fastener failure or stripout of the work surface

The fastener is fully seated when the head's bearing surface is flush with the cabinet.

NOT Recommended for use with treated wood.

ALL PRIMESOURCE® FASTENERS ARE MANUFACTURED IN AN ISO 9001 CERTIFIED AND APPROVED FACTORY TO PRIMESOURCE® PERFORMANCE SPECIFICATIONS AND PRINT DRAWINGS.



SAFETY DATA SHEET

These products do not meet the criteria of hazardous chemicals as defined by the Federal Occupational Safety and Health Hazard Communication Standard 29CFR 1910.1200(c). This form is provided solely as general information and should not be construed as a determination that the product(s) are hazardous chemical(s).

GENERAL INFORMATION

Dated: October 24, 2024
Distributor: Pro-Twist brand
PrimeSource Building Products
1321 Greenway Drive
Irving, TX 750335

PRODUCT INFORMATION

Product Name: Metal Fasteners (Screws, Nails, Collated Screw, etc.)

TYPICAL CHEMICAL COMPOSITION

Substrate: Various Ferrous Metals
Coatings: Various; Zinc Plating, Phosphates, Organic

PHYSICAL DATA

Physical State:	Solid	Specific Gravity:	7.6 – 7.8
Appearance:	Various Shapes	Vapor Pressure:	N/A
Boiling Point:	N/A	Vapor Density:	N/A
Melting Point:	Greater than 1400°F	Evaporation Rate:	N/A
Solubility in Water:	N/A	Volatile by Volume:	N/A
PH:	N/A	Odor:	None

FIRE AND EXPLOSION HAZARD DATA

Not Applicable

1321 Greenway Drive • Irving, Texas 75038 • 800-676-7777 • www.PrimeSourceBP.com





REACTIVITY DATA

Stability:	Stable
Hazardous Decomposition Products:	CO ₂ and/or CO
Incompatibility – Materials to Avoid:	Strong Mineral Acids, Alkali or Oxidizers
Polymerization:	Will not occur

HEALTH HAZARD DATA

Health Effects/Signs & Symptoms:	N/A
Usual Route(s) of Entry:	Sharp metal fastener may cut skin
Medical Conditions Possibly Aggravated:	None Known
Carcinogen Information:	None Known
Eye Contact:	Not anticipated to pose a significant eye hazard
Skin Contact:	Not anticipated to pose a significant skin hazard
Ingestion:	Not anticipated to pose a significant ingestion hazard
Inhalation:	Not considered an inhalation hazard

OCCUPATIONAL EXPOSURE CONTROL MEASURES

Eye Protection:	Safety glasses recommended
Skin Protection:	Gloves recommended
Ingestion:	Never place fasteners in mouth

SPILL, LEAK AND DISPOSAL INFORMATION

Procedures to Follow if Material is Released or Spilled:	N/A
Waste Disposal Method(s):	Any excess product can be recycled for further use or disposed of by methods which are in accordance with local, state and federal regulations.

ADDITIONAL OR MISCELLANEOUS INFORMATION

After working with coated materials, wash hands and face before eating, drinking or smoking.
Characteristics not covered on the SDS are not applicable to this material at this time.

1321 Greenway Drive • Irving, Texas 75038 • 800-676-7777 • www.PrimeSourceBP.com

