TECHNICAL DATA

COLLATED FINE THREAD DRYWALL SCREW

For attaching gypsum board to 25-20 gauge steel studs.

PRODUCT SPECIFICATIONS

Part #	Length	Point	Gauge	Bit Size
FS114C1M	1-1/4	Sharp Point	#6	#6
FS114C4M	1-1/4	Sharp Point	#6	#6
FS118C4M	1-1/8	Sharp Point	#6	#6
FS158C1M	1-5/8	Sharp Point	#6	#6
FS158C4M	1-5/8	Sharp Point	#6	#6
FS6200C1M	2	Sharp Point	#6	#6
FS6200C4M	2	Sharp Point	#6	#6

	Size	4M	1M
Black Phosphate	6 x 1″	–	FS100C1M
	6 x 1-1/8″	–	FS118C1M
	6 x 1-1/4″	FS114C4M	FS114C1M
	6 x 1-5/8″	FS158C4M	FS158C1M
	6 x 2″	FS6200C4M	FS6200C1M
	7 x 2″	–	FS200C1M
Zinc	6 x 1″	–	FSZ100C1M

- Bugle Head
- #2 Phillips Recess Drive
- Sharp Point
- Coarse Thread
- Available in Black Phosphate or Zinc
- Made to conform to ASTM C1002

For fastener technical assistance call 800-676-7777

ALL PRIMESOURCE® FASTENERS ARE MANUFACTURED IN AN ISO 9001 CERTIFIED AND APPROVED FACTORY TO PRIMESOURCE® PERFORMANCE SPECIFICATIONS AND PRINT DRAWINGS.

© 2025 PrimeSource® Building Products, Inc