PRIMESOURCE BUILDING PRODUCTS, INC.

SPEC DATA *Submittal Sheet # 043*

EYELAGS - SHARP POINT

Interior ceiling systems into Wood. Primarily used for hanging suspended ceiling grid into wood joists. Longer length for drywall (or insulation) into Wood.





Product Specifications

Part #	Dia.	Length	TPI	Bulk Qty	Hole Dia.	Point	Finish
EL3	1/4”	3”	10	1M	3/16”	Sharp	None
EL4	1/4”	4”	10	1M	3/16”	Sharp	None
EL5	1/4”	5”	10	1M	3/16”	Sharp	None

Eyelag Sharp Point Screws Ultimate Connection Value Chart		
Nominal Screw Dia. (in)	Wood Type	Tension (Pull Out) Lbs
1/4”	Redwood	482
	Fir	503

Ultimate Value Chart

Eyelags were driven into wood then pulled out with testing machine.

Note that all results were obtained in strict adherence to ASTM test protocol. These ultimate figures are offered only as a guide and are not guaranteed in any way by PrimeSource Building Products.

A 4:1 safety ratio is recommended.

ALL PRIMESOURCE FASTENERS ARE MANUFACTURED IN AN ISO 9002 AND ISO 14001 CERTIFIED AND APPROVED FACTORY TO PRIMESOURCE PERFORMANCE SPECIFICATIONS AND PRINT DRAWINGS.

©2016 PrimeSource Building Products, Inc.