PRIMESOURCE BUILDING PRODUCTS, INC.

# SPEC DATA *Submittal Sheet # 009*

## LAMINATING SCREW

Originally designed for temporary drywall to drywall applications.

Also used to attach drywall to wood.






Meets ASTM C-1002

Reduced #2 Phillips

## Product Specifications



| Part # | Dia. | Length | TPI | Bulk Qty | Finish | Head | Head Dia. | Corrosion | Thread | Point |
|---|---|---|---|---|---|---|---|---|---|---|
| LS10112 | 10 | 1-1/2 | 8 | 5M | Phos. | Bugle | 8.5mm ~ 9.2mm | 48 hr. min. B-117 | Single lead | Piercing 25° |

**Pro-Twist sharp multi-purpose screws Meet or Exceed ASTM C-1002 and/or ASTM C-1513**

**LS10112 qualifies as a Type G fastener in accordance with ASTM C-1002**

| Laminating Self-Piercing Point Screws Ultimate Values | | | | | |
|---|---|---|---|---|---|
| Dia. | Pull-Out 2x4 Red Wood | Pull-Out 3/4 Particle Board | Pull-Out 2x4 Fir | Pull-Out Plywood | Minimum Torsional Strength (Lb) |
| 10 | 587 | 388 | 563 | 466 | 56 |

Ultimate Value Charts

Wood - Screws driven 3/4” into the wood material, then pulled out the testing machine.

Note that all results were obtained in strict adherence to ASTM test protocol. These ultimate figures are offered only as a guide and are not guaranteed in any way by PrimeSource. A 4:1 safety ratio is recommended.

Installation Guidelines

0-2500rpm Screwgun with torque adjustment - Overdriving may result in fastener failure or stripout of the work surface

The fastener is fully seated when the head’s bearing surface is flush with the drywall

NOT Recommended for use with treated wood.

**ALL PRIMESOURCE FASTENERS ARE MANUFACTURED IN AN ISO 9002 AND ISO 14001 CERTIFIED AND APPROVED FACTORY TO PRIMESOURCE PERFORMANCE SPECIFICATIONS AND PRINT DRAWINGS.**



©2016 PrimeSource Building Products, Inc.